DUCT FANS



BSKF AC RECTANGULAR IN LINE DUCT FANS Forward Curved

Bahcivan Brand Rectangular In-Line Duct Fans engineered for medium and large ventilation needs where space is at a premium. BSKF Rectangular fans developed and manufactured for higher pressure performance, trouble-free, and direct-to-duct operations. The motorized impeller is mounted on a hinged door - the user just swings the door out for easy access to the impeller for maintenance.


Technical Drawings


MATERIAL

INSULATION CLASS DIRECTIVE SPEED CONTROL

APPLICATION AREAS

- : The housing and impeller are galvanized sheet steel.
- : Class F
- : EN 60335-1, EN 60335-2-80
- : Speed can be adjusted using an optional controller.
- : BSKF series fans are perfect for for commercial and industrial Ventilation use.





	AGE	FREQUENCY	ER	CURRENT	CAPACITOR	Ω	FLOW	VD SSURE L	HT
	VOLTAGE		POWER	-		SPEED	AIR	PRES	WEIGHT
ТҮРЕ	V	Hz	W	(A)	(µF)	d/d	m³/h	dB(A)	kg
BSKF 40-20	230	50	195	0,9	6	1420	990	58	14
BSKF 50-25	230	50	450	2	8	1395	1750	70	19
BSKF 50-30	230	50	590	2,6	14	1370	2100	72	23
BSKF 60-30	380	50	1320	2,7	-	1390	2950	75	36
BSKF 60-35	380	50	2630	1,5	-	1485	4250	70	44

TYPE	А	В	С	D	Е	F	G
BSKF 40-20	198	398	502	420	220	440	240
BSKF 50-25	248	498	532	520	270	540	290
BSKF 50-30	298	498	562	520	320	540	340
BSKF 60-30	298	598	642	620	320	640	340
BSKF 60-35	348	600	720	620	370	650	390



